

Westover Church Worship Center Technical Specifications

(Information is accurate as of 10/02/2007)

Stage

General Information: Stage is a proscenium thrust

Proscenium Width: 88'

Proscenium Height: 34' 8"

Total Stage Width: 155' 7"

Wing Size: 38' (stage left) 30' (stage right)

Stage Depth: 32' (proscenium to back wall)

Apron Depth: 40' in center; 18' on sides; 24' without pit filler

Orchestra Pit: 16' x 76'

Grid Height: 44'

Stage Height: 42"

Loading Access: Stage Lift elevator located upstage center, travels to dock level. 9' x 9' x 22'

Stage floor surface: Pine painted satin black; screws permitted

Risers: Available upon request

Rigging

Linesets: 9 motorized, fixed speed, variable positioning
See lineset schedule for details.

Battens: 2500 lb box trusses

Main Curtain: curved Braille

Curtain Hang: 3 sets of legs, 3 borders, 1 midstage traveler, full stage rear cyc

Motor Control: controls located stage right; 75' pendant for remote

Hang Points downstage

of Proscenium: tension grid, steel, 10,000 lb capacity

Additional Hang Points

Behind Proscenium: steel 15,000 lb capacity

Lighting

Dimming: ETC Sensor + 384 dimmers (including houselights)

Control: Jands Vista; Unison architectural

Control Locations: booth, middle of house, stage

Electrics: 3 overstage, wall pockets on stage and in pits

Front Of House: 3 catwalks, tension grid, side balconies

Moving Lights: (6) VL3000; (6) VL3500; (2) DL1

Other: Catalyst Media Server

Conventional Fixtures: Source4 Elipsodials, Wybron Nexeras, Focusing Cycs, Selecon Pacific's

Follow Spots: 2 Robert Juliet Buxies (575 watt) located in catwalk. Additional follow spot locations at the rear of the upper balcony

Show Power: 2 400 amp disconnects (lighting)
1 400 amp disconnect (audio ground) all Camlocks

Shore Power: 1 100 amp, 1 400 amp disconnects for truck/bus power located at the drive under

Westover Church Worship Center Technical Specifications

(Information is accurate as of 10/02/2007)

Sound

Custom Acoustics: All auditorium wall and front balcony surfaces are covered with acoustic or vari-trap panels. Main and balcony ceilings are treated with Barisol membrane panels.

Front Of House: Midas XL8 Live Performance System;
96 channels (80 inputs onstage)

Tascam CD-O1U playback deck

Tascam CD-RW901 record deck

Software – EV IrisNet®, SmaartLive®, Shure Wireless Workbench

Flying Rack System: 6 Midas DL 451 I/O boxes for outside tour console interface into house audio network or house truck panel.

Speaker Face: EV Xi-1183 and Xi-1123 (mains)
EV 1082 (front fill; over and under balcony fill)
EV X-sub (stage)
EV QRX 118S subs (over balcony)
EV Evid 6.0 (surrounds)
All custom tuned for room

Amplifiers: EV 3000, 1200 and 900 RL series, EV 7100 (surrounds)
EV NetMax audio matrix

Monitoring: While all of our stage monitoring is from FOH, we have the system interface and connectivity for touring stage monitor consoles.

Stage Monitors: IEM Aviom Personal Monitoring System
(4) Shure PSM600 and (2) Shure PSM 400 wireless systems
(6) wired systems, (8) EV QRX 112/75 wedges
ButtKickers® for drum, bass and keyboard portable risers

Microphones: (12) Shure UHF-R wireless systems, (6) KSM9 capsules
(6) Beta 87 capsules
(12) UR-1 bodypacks, (12) EV RE 97's, (6) Shure Beta 87's wired
(10) Shure SM 58's wired, (3) Shure SM 57's wired
(6) Audix M 1245 Microboom choir mics
(2) Sony ECM 999 stereo mics, (2) AKG 3000's, 2 AKG 1000's
(3) Audio Technica Pro 35x clip on's, (3) Audio Technica Pro 37R's
(1) Audio Technica 4047
(2) Sennheiser E 609 mics with guitar cab ISO boxes
(2) Crown PZM's
(6) Beyerdynamic MCE 86S shotgun mics (4 for audience response)
(2) Audix SCX-25's

Drum Microphones:

(3) Audix Micro-D's, (1) Audix i5, (2) Audix SCX -25's, (1) Sony ECM-999
(1) Shure SM 57, (1) Shure SM 81, (1) Shure Beta 91
(1) Shure Beta 52, (1) EV ND 868

Backline: (4) Countryman DT 85 DI's, (3) Klark-Teknik DN 100 DI's
(20) K&M boom mic stands, (3) K&M mini-boom stands
14-channel mixer on drum riser to insert playback sources
for loops and click tracks

Westover Church Worship Center Technical Specifications

(Information is accurate as of 10/02/2007)

Sound (continued)

House Drum Kit: DW Blue Diamon Pearl, 6-ply maple toms and 8-ply maple kick
18x22 Kick Evans Emad Clear (with G3 Resonant white front head)
10x9 (all toms Evans G2 coated; G1 Resonants clear), 12x10, 14x12,
16x14 all available
Stands for (3) crashes, ride, splash, and hats
Black Panther maple snare 6x14 power stroke coated on all snares
Pearl Masters maple snare 5x15

Audio Production: DAW Workstation, Sonar Producer Edition 6, Midas Verona 480 (can be used for stage monitor console)

Video

Image Magnification Stewart Filmscreen 13.5'x24' (16:9 aspect ratio)

(IMAG) screens: rear projection surface

Projection: Christie Roadster S+12K, SXGA+, 12,000 lumen, 3-chip DLP

IMAG Switching: Sony DFS-700

Source devices: DVD, DVCAM videotape, Insciber® Studio SD

Furniture: Marco consoles

Production

Cameras

(IMAG/Production): 4 Sony DXC-D50WSL; 1 Sony DXC-D35WSL

Camera connectivity: 14 Triax locations in Worship Center
6 Triax locations in other parts of the building
6 Triax tie lines to production truck panel

Camera control: Sony CCU D-50 camera control units supporting dual tally indicators

Camera support: 2 Slik Broadcast with Daiwa heads
3 CSI models

Production Switcher: Echolab Nova 1716 (16 I/O, 1.5 M/E switcher, SDI format)

Monitoring: 2 Wall-mounted Samsung 46" LCD

Camera/Source

monitoring: Leitch Neo SuiteView™ display processor

Graphics: Insciber® Studio SD

Recording: DVCAM format on Sony DSR-45 VTR; DVD format on Pioneer PVR-LX1; MPEG-2 on Doremi Labs V1MP2 DDR

Playback sources: DVCAM format, DVD, PC, Doremi DDR

Audio console: Midas Venice, 32-channel (from existing building)

Engineering router: Leitch Integrator 64x64ST8 SDI

Engineering monitor: Sony high resolution CRT style (model TBD)

Intercom: Telex Audiocom, 6 Channels routable to 48 locations including rehearsal spaces, WAV offices and 2 wireless stations.

CCTV Headend: Blonder-tongue distribution, channel filter and insertion equipment

Video processing Videotek, Extron (CAT5 & scan conversion),
and distribution: Kramer and Leitch components (AJA A/D & D/A conversion)

Furniture: Marco consoles

Intercom

Intercom: Telex, 6 channels, wired and wireless